



LE SPÉCIALISTE EN TOILES ET FILETS

TECHNICAL SHEET / FICHE TECHNIQUE

MÉGATEX

POLY 1577

General description : High density polyethylene woven fabric base complete with a low density coating.

Denier of type	1200D	
Construction	Warp 15 / weft 15	
Coating	3mil / both sides	
Weight	7.6oz p.s.y	
Tensile Grab strength	192/184	Fed 191 method 5100
Grab tear	Warp 25 /weft 22	Fed 191 method 5100
Busrt	500 PSI	
Puncture	125 lbs	
Thickness	14 mil	
Standart width	74``	
Standart colours	Silver/ black	

Weatherebility : special UVI treatment gives 80% strength retention after 2000 hours on a weatherometer.

General properties : The outstanding characteristics of this product are :

- 1) Wear – the thick, heavy coating and tight weave give this material high wear and puncture proterties compared to the P.E fabrics.
- 2) Ultra-violet resistance – treated for long life in permanent outdoor exposure.

We believe this information is the best currently available on the sibject. We make no guarantee of results and assume no obligation or liability in connection with this information. It is offered as a possible helpful suggestion in any experimentation you may care to undertake along these lines.

Mégatex inc.

2800 rue Dalton, suite 1, Québec (Ste-Foy) Qc. G1P 3S4

Tél. : (418) 651-2800 Fax : (418) 651-6755

Courriel : info@megatex.ca
ventes@megatex.ca