



LE SPÉCIALISTE EN TOILES ET FILETS

TECHNICAL SHEET / FICHE TECHNIQUE

MÉGATEX

RB6-6

TYPE RB6-6

DATA SHEET

DESCRIPTION Developmental material intended for use in crop covers and
Other protective applications.

FABRIC SPECIFICATIONS

Weave	Woven black HDPE scrim using 1600 denier tapes
Coating	2.0 mil average each side (47 g/m ² /side)
Colour	Black or coloured coating available
Weight	5.8oz / yd ² (197 g/m ²) +/- 5%
Thickness	10 mils (0.25mm) ASTM D5199

PERFORMANCE

Grab tensile	Warp 210 lbs 933N Weft 145 lbs 645N	ASTM D5034
tongue tear	Warp 45lbs 200N Weft 50lbs 222N	ASTM D2261
Mullen burst	270 PSL 1860 Kpa	ASTM D751
Accelerated UV weathering	80% strength after 2000 hrs ¹ Q.U.V. (A-340 Lamps): 8 hrs UV @ 60° C; 4hrs condensation @ 50° C	ASTM G53

ROLL SPECIFICATIONS

Cores	4 inch (101.6mm) or 5 inch (127 mm) I.D
Width	Up to 144 inches (-0, +0.5) as ordered 3.66m (-0,+12mm)
Length	Minimum 500 yds/roll (457m) up to 1000 yds/roll (914m)

These values are based on limited data and will be revised as more becomes available.

Mégatex inc.

2800 rue Dalton, suite 1, Québec (Ste-Foy) Qc. G1P 3S4

Tél. : (418) 651-2800 Fax : (418) 651-6755

Courriel : info@megatex.ca

ventes@megatex.ca