



LE SPÉCIALISTE EN TOILES ET FILETS

FICHE TECHNIQUE ME-1BTLBW 10X 5 BKFR

This product is a mesh fabric comprised of 22 % high tenacity polyester yarn and 78 % flexible foamed PVC. The yarns are intimately bonded at the crossover points and the degree of openness is dependent on the fabric construction

Construction	10X5 ENDS/INCH
COATING	FLEXIBLE FOAMED PVC
CORE YARN	1000 DENIER POLYESTER
FABRIC WEIGHT	7.4 OZ/SQ YARD
TENSILE STRENGTH (ASTM D-1682) GRAB	WARP : 136 LBS/ INCH MINIMUM FILL : 44 LBS/INCH MINIMUM
TEAR STRENGTH (ASTM D-2261) TONGUE SINGLE RIP	13.1 LBS MINIMUM WARP 5.9 LBS MINIMUM FILL
MULLEN BURST STRENGTH (ASTM D-3786)	157 LBS/ SQ INCH MINIMUM
FIRE RETARDANCY	AS REQUIRED AFTER FLAME : LESS THAN 3 SEC CHAR LENGTH : LESS THAN 4 SEC
COLD CRACK	NO CRACKING AFTER 24 HOURS
UV RESISTANCE (ASTM G53)	1000 HOURS QUV EXPOSURE- SLIGHT COLOR DETERIORATION
SPECIFIC GRAVITY	0.60
TYPICAL APPLICATION	HIGH STRENGTH BARRIER PROTECTIVE NETTING

Note : Above values represent typical data and are subject to slight variations. No warranty is expressed or implied regarding the accuracy of these data.

Mégatex inc.

2800 rue Dalton, suite 1, Québec (Ste-Foy) Qc. G1P 3S4

Tél. : (418) 651-2800 Fax : (418) 651-6755

Courriel : info@megatex.ca

ventes@megatex.ca



LE SPÉCIALISTE EN TOILES ET FILETS

Mégatex inc.

2800 rue Dalton, suite 1, Québec (Ste-Foy) Qc. G1P 3S4

Tél. : (418) 651-2800 Fax : (418) 651-6755

Courriel : info@megatex.ca
ventes@megatex.ca