



LE SPÉCIALISTE EN TOILES ET FILETS

Megatex Mesh pvc 3/16 x 3/16 Fr noir

BO-LOC mesh fabrics comprised of 22% high tenacity polyester yarn and 78% flexible foamed pvc. The yarns are intimately bonded at the crossover points and the degree of openness is dependent on the fabric construction.

Construction	10x5 ends/inch
Coating	Flexible PVC (73%)
Core yarn	1000d polyester (27%)
Tensile strenght (ASTM D-1682) Grab	Warp : 19lbs/ inch minimum Fill : 108lb/ inch miminum
Tear strength (ASTM D2261) Tongue single rip	39 lbs minimum warp 33 lbs minimum fill
Mullen burst strength (ASTM D3786)	211 lbs/ sq in minimum
Fire retardancy	As required
Uv resistance (ASTM G53)	1000 hours QUV exposure- slight olor deterioration (not applcable for fluorescent colors)
Standart colors	Black
Typical Applcations	Swimming pool barriers, safety netting, debris netting

Please note : above values represent typical data and are subject to slight variations. No warranty is expressed or implied regarding the accuracy of this data.

Mégatex inc.

2800 rue Dalton, suite 1, Québec (Ste-Foy) Qc. G1P 3S4

Tél. : (418) 651-2800 Fax : (418) 651-6755

Courriel : info@megatex.ca

ventes@megatex.ca